80KA FOR 1 SECOND

AVAILABLE THE FOLLOWING RATINGS 1600A

100KA FOR 1 SECOND

AVAILABLE THE FOLLOWING RATINGS 3200A 4000A

5000A 6300A rolla.co.uk

2500A FULLY COMPLIANT WITH **BS EN 61439-2**

(IEC 61439-2)

ROLLA'S **DSB** range is a 1340mm deep ultimate integrity form 4 MODULAR DISTRIBUTION BOARD.

THE COMPLETE ${f DSB}$ range has been type tested in conjunction with ABB TO THE LATEST INDUSTRY STANDARD, INCLUDING ICW, ICC & TEMPERATURE RISE.

THE $\overline{\mathbf{DSB}}$ range is supplied as 1P31, naturally ventilated, without the NEED FOR DERATING. THIS INCLUDES THE ABB E4.2 4000A ACB IN A 900 WIDE CABINET & THE ABB E6.2 6300A ACB IN A 1300 WIDE CABINET. ALL OF THIS HAS BEEN TESTED IN THE MOST ONEROUS ARRANGEMENT, i.e. WITH THE MAIN BAR SYSTEM AT THE BOTTOM.

THE **DSB** range is manufactured from fully welded 3mm sheet steel. WITH EITHER GALVATITE OR ALUMINIUM GLAND PLATES TO SUIT INDIVIDUAL APPLICATION NEEDS.

DSB busbars are available as hdhc plain or tinned copper.

THE $\overline{\mathbf{DSB}}$ range is painted in-house & is available in any BS4800 or RAL SHADE OF PAINT COLOUR.

The fundamental ${f DSB}$ sections are supplemented with a range of ADDITIONAL FEATURES. FOR EXAMPLE, CABLE BOXES, CORNER SECTIONS. OVERHEAD BUSBAR BRIDGE SECTIONS & TRANSFORMER HOUSINGS. A WHOLE RANGE OF ANCILLARY PARTS ARE AVAILABLE TO TAILOR YOUR DISTRIBUTION BOARD TO ALL PROJECTS REQUIREMENTS.

THE DOORS & CHASSIS FOR ALL THE COMPARTMENTS ARE PRE PUNCHED TO SUIT YOUR CHOSEN DEVICES. YOU THEN FREE ISSUE THE DEVICES TO BE MOUNTED & BARRED IN HOUSE BY US.